



Material safety data sheet
Revised 03/24/03

Section 1

Manuf/Dist. name:
 Company Address:

Company phone:
 Emergency phone:

Trade name:

Part Number:

Chemical name:

Chemical Family:

Formula:

Product code:

Manufacture Information

Danny's Dealer Supplies Inc.
 1037 Okeechobee Rd. Unit 1
 West Palm Beach Fl. 33401
 561-822-9994 Fax 561-655-1522
 800-535-5053 Infotrac 24 hours Medical information

Leather Care

Dds.405

Not Applicable

Not Applicable

Proprietary

Not Applicable

Hazardous material identification

Product name:

Hazard rating:

Leather Care

Dds.405

0 = Insignificant

1 = Slight

2 = Moderate

3 = High

4 = Extreme

* = Special

Health	0
Fire	0
Reactivity	0
Specific	

Section 2

Hazardous ingredients

Hazardous ingredients

See CFR29 § 1910.1200 (i)-(13)

Chemical name

CAS number

Percentage

PEL-OSHA

TLV-ACGIH

No hazardous components

Carcinogens

NTP: not listed

OSHA: not listed

IARC Monograph: no listed

Section 3

Effects of overexposure First aid procedures

Health effects acute and chronic

Eyes:

Can cause severe irritation, redness, tearing, blurred vision.

Skin:

Prolonged and repeated contact can cause moderate irritation, defatting, dermatitis.

Ingestion:

Can cause gastro intestinal irritation, nausea, vomiting and diarrhea.

Inhalation:

Can cause mild irritation.

Chronic:

Inhalation may increase susceptibility to respiratory illness.

Emergency First aid procedures

Eyes:

Flush with plenty of water for 15 minutes.

Skin:

Immediately flush skin with plenty of running water for 30 minutes. Remove contaminated clothing and wash before reusing.

Ingestion:

Do not induce vomiting. Call physician immediately. Drink copious amounts of water or milk, consult physician.

Inhalation:

Breathe fresh air. Administer oxygen if breathing is difficult.

Contact a physician if problem continues.

For emergencies contact Infotrac 800-535-5053

Section 4**Physical data**

Appearance	White crème
Odor	Leather
Solubility in water	Soluble
Vapor pressure mm hg	ND
Boiling/melting point (F)	212°F
Vapor density (air=1)	ND
Evaporation rate (butyl acetate=1)	ND
Percentage volatile by weight (%)	ND
Specific gravity (water-1)	1.01

Section 5 Fire, Explosion and Reactivity hazard data

Flash point °F	None
Flammability limits in air (%V)	LEL-ND UEL-ND
Extinguishing media	Non-flammable
Special fire fighting procedures	SCBA should be used in fighting fires involving chemicals.
Unusual fire and explosion hazards	See Hazardous decomposition products
Chemical incompatibility	None
Hazardous decomposition products	Burning may produce carbon oxides, and silicone oxides.
Hazardous polymerization	Will not occur.
Stability	Stable

Section 6 Spill or leak procedures Waste disposal method

Spill or leak procedures	Absorb large spills with suitable absorbent. Shovel into containers. Wash residue with water.
Waste disposal method	Dispose of according to local, state and federal regulations.

Section 7 Precautions for safe handling and use

Respiratory	None required for local use
Ventilation	Local exhaust recommended
Eye protection	Safety glasses should be worn in all industrial operations.
Handling instructions	Avoid eye contact and prolonged contact with skin. Wear protective gloves. Use adequate ventilation. Wash thoroughly after handling.
Work practices	Eye wash fountain and safety shower should be easily accessible. Provide adequate ventilation.
Hygienic practices	Avoid contact with eyes, skin and clothing.

Section 8**Special precautions**

Handling precautions	Do not store under freezing conditions. Protect from physical damage. Keep away from open flame.
Maintenance precautions	When working with flammable material electrically ground all equipment.
Other precautions	Containers even those that have been emptied will retain product residue and vapors. Always obey hazard warnings and dispose of containers according to state or local guidelines.
Additional precautions	None

KEEP OUT OF REACH OF CHILDREN